



**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
57 Assembly Drive  
Tullamarine Victoria Australia 3043

**Telephone** + 613 9335 3333  
**Facsimile** + 613 9338 9260  
**Email** melb@emctech.com.au  
**www.emctech.com.au**

Radio Frequency Fields Survey  
at  
Burwood Campus  
221 Burwood Hwy, Burwood, Vic 3125  
  
For  
Deakin University  
  
EMC Technologies Report No. M060726  
  
Date: 28<sup>th</sup> August 2006



NATA Accredited  
Laboratory  
Number: 5292

The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full.

**Radio Frequency Fields Survey  
at  
221 Burwood Hwy, Burwood**

**Report Number: M060726**

**Site Address:** 221 Burwood Hwy  
Burwood, Vic 3125

**Client:** Deakin University  
**Address:** Melbourne Campus  
Burwood, Vic 3125

**Contact:** Michael O'Donoghue  
**Phone:** (03) 9246 8175

**Survey Dates:** 20<sup>th</sup> July 2006

**Exposure Standard:** *the Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz (2002)-RPS3, published by the Australian Radiation Protection and Nuclear Safety Agency (ARPANSA).*

**Measurements  
Performed by:**



**Justin McLoughlan**

**Authorised Signatory:**



**Aaron Sargent**  
**EMR Engineer (BEng)**



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



# Radio Frequency Fields Survey At 221 Burwood Hwy, Burwood

## 1.0 INTRODUCTION

The purpose of this survey was to measure the Radio Frequency (RF) field levels at Deakin University, Burwood Campus, 221 Burwood Hwy, Burwood, Vic 3125.

This report contains the results of the broadband RF Electromagnetic Radiation (EMR) measurements conducted at various locations around the university on the 20<sup>th</sup> of July 2006.

The RF fields were compared against the limits of *the Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz (2002)*-RPS3, published by the Australian Radiation Protection and Nuclear Safety Agency (ARPANSA). The provisions of the ARPANSA standard are mandated by the Australian Communications and Media Authority (ACMA) to protect the general public from over-exposure to RF fields from radio transmitters.

The RF field measurements were performed in accordance with EMC Technologies NATA accreditation, using appropriate measurement equipment and procedures.

The terms electromagnetic radiation (EMR) and electromagnetic energy (EME) have the same meaning when used in this report.

## 2.0 EXECUTIVE SUMMARY

### Compliance with ARPANSA Radiation Protection Standard No 3

All measured RF field levels at the specified locations at the school were below the recommendations specified in the ARPANSA standard for general public/non-occupational exposure. The highest level recorded was 0.3186% of the limit.

## 3.0 SCOPE OF THE MEASUREMENTS

Broadband RF Field measurements were performed in the frequency range 100kHz to 3.0 GHz for Electric (E-Field) in units of Volts per metre (V/m). The levels recorded were then converted to Power Density in Watts per metre squared ( $W/m^2$ ) and compared against the reference levels (limits) specified by the ARPANSA standard.

All results in this report are indicative only of the time they were recorded, as RF Field levels are dependent on the actual telecommunication traffic at the time of the measurement.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd  
[www.emctech.com.au](http://www.emctech.com.au)



## 4.0 THE AUSTRALIAN STANDARDS, REGULATIONS & DEFINITIONS

### 4.1 Reference Standards and Regulations

#### **Portable Devices and Mobile Stations**

The *Australian Communications Media Authority (ACMA) Radiocommunications (Electromagnetic Radiation - Human Exposure) Standard 2003* is the mandatory standard for equipment compliance with the *Radiocommunications Act 1992*. It refers to the provisions of the ARPANSA standard and applies to handheld and portable RF transmitting devices such as mobile phones, walkie-talkies, WLAN devices, and similar devices using RF transmitters.

#### **Apparatus and Transmitters**

The *ACMA Radiocommunications Licence Conditions (Apparatus Licence) Determination 2003* sets out the conditions for the licence to operate transmitting equipment. It mandates the General Public/non-occupational provisions of the ARPANSA standard. Further information can be gained from the ACMA web site: <http://www.acma.gov.au/standards/index.htm>.

#### **Human Exposure Standard**

The *Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz (2002)*, referred to as the ARPANSA standard, sets limits for human exposure to RF fields to prevent adverse health effects. The ARPANSA Standard specifies basic restrictions for occupational and general public exposure. It also stipulates equipment and usage parameters in order to assist in the determination of compliance with the specified limits.

#### **RF Field Measurements and Evaluations- Methodology**

The *Australian Standard AS 2772.2:1988 Radio Frequency Radiation, Part 2: Principles and Methods of Measurements – 300kHz to 100GHz*, specifies techniques and instrumentation for the measurement of potentially hazardous electromagnetic sources. The measurements were performed in accordance with this standard.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd  
[www.emctech.com.au](http://www.emctech.com.au)



## 4.2 Definitions

### Basic Restrictions

Mandatory limits on exposure to RF fields are based on established health effects and are termed 'Basic Restrictions'. Protection against adverse health effects requires that these Basic Restrictions are not exceeded. However, these mandatory Basic Restrictions are impractical to measure, therefore, a set of Reference Levels utilising quantities much easier to measure was established as an alternate means of compliance with the Basic Restrictions.

### Reference Levels

The Reference Levels were conservatively formulated such that conformity with these Reference Levels will ensure compliance with the Basic Restrictions. The Reference Levels cited in the report are measured as quantities of Volts per metre (V/m), Amps per metre (A/m) and Watts per square metre ( $W/m^2$ ).

### General Public/Non-Occupational Exposure

Exposure of persons, other than in the course of or intrinsic to their work. This category includes persons of all ages and health status who will be generally unaware that exposure is taking place. The exposure of the general public and workers in the precincts of the area surveyed is regarded as General Public/Non-occupational exposure

### Occupational Exposure

Exposure under controlled conditions, in the course of and intrinsic to the nature of their work, of a population consisting of adults who are trained or informed to be aware of potential risks and to take appropriate precautions. The duration of occupational exposure is limited to the duration of the working day or duty shift per 24 hours and the duration of the working lifetime. This category excludes pregnant workers, who must not be exposed at levels in excess of the non-occupational limit.

## 4.3 Exposure Limits – Reference Levels

The ARPANSA standard defines the limits of exposure in terms of Power flux density, Electric and Magnetic fields for the relevant frequency. Compliance with the Basic Restrictions is presumed if the Reference Levels are not exceeded.

Levels cited in the report are measured as quantities of Watts per metre squared ( $W/m^2$ ).

**Table 1: Extract from Table 7 of the ARPANSA RPS3 Standard**

Frequency Range (f)	General Public Limit ( $W/m^2$ )
10 MHz – 400MHz	2
400MHz – 2,000MHz	$f / 200$
2,000MHz – 300,000MHz	10

Note: f is the frequency in MHz

The most conservative limit (10MHz – 400Mhz range) has been applied to the measured levels. The recorded values will be compared to the limit of  $2 W/m^2$  in this report.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



## 5.0 MEASUREMENT EQUIPMENT

**Table 2: Equipment Details**

Equipment	Model	Freq. Range	Last Cal	Cal Due
Broadband Probe E Field	EMR 300	100kHz – 3.0 GHz	07/04/2006	07/04/2008

### Measurement Uncertainty

The following measurement uncertainty has been conservatively determined in accordance with ISO17025 and NATA requirements.

Broadband E-field Measurement Uncertainty:

Broadband Probe	$\pm 1.2$ dB
Environmental	$\pm 1.8$ dB (Worst case)
<b>Total:</b>	<b><math>\pm 3.0</math> dB</b>



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



## 6.0 MEASUREMENT PROCEDURE

Broadband RF EMR measurements were made using the Wandel and Golterman (now called NARDA) EMR-300 Electric Field Strength meter. Measurements were performed at head height (approx 1.8m) unless otherwise specified.

### 6.1 Measurement Positions

Measurements were performed in most generally accessible areas of the Deakin University, Burwood campus, located at 221 Burwood Hwy, Burwood, Vic 3125. See Table 3 for a list of all measurement positions. Refer to Appendix B for diagrams of measurement positions.

## 7.0 RESULTS OF RF FIELDS MEASUREMENTS

### 7.1 Broadband Results

The broadband RF field strengths measured are listed in the following table. All measurements were taken at head height (approx 1.8m) unless otherwise stated. The measurement sensitivity of the Narda field probe was 0.1326% of the Reference Level.

**Table 3: Broadband Results**

Pos	Position Level	Power Density W/m <sup>2</sup>	Limit W/m <sup>2</sup>	% of Limit W/m <sup>2</sup>
1	Level 5	< 0.002653	2.00	< 0.1326%
2	Level 4	< 0.002653	2.00	< 0.1326%
3	Level 3	< 0.002653	2.00	< 0.1326%
4	Level 2	< 0.002653	2.00	< 0.1326%
5	Level 1	< 0.002653	2.00	< 0.1326%
6	Level 3	< 0.002653	2.00	< 0.1326%
7	Level 3	< 0.002653	2.00	< 0.1326%
8	Level 2	< 0.002653	2.00	< 0.1326%
9	Level 1	< 0.002653	2.00	< 0.1326%
10	Level 1	< 0.002653	2.00	< 0.1326%
11	Level 2	< 0.002653	2.00	< 0.1326%
12	Level 2	< 0.002653	2.00	< 0.1326%
13	Level 3	< 0.002653	2.00	< 0.1326%
14	Level 3	< 0.002653	2.00	< 0.1326%
15	Level 2	< 0.002653	2.00	< 0.1326%
16	Level 1	< 0.002653	2.00	< 0.1326%
17	Ground	< 0.002653	2.00	< 0.1326%
18	Level 1	< 0.002653	2.00	< 0.1326%
19	Ground	< 0.002653	2.00	< 0.1326%
20	Level 1	< 0.002653	2.00	< 0.1326%
21	Level 1	< 0.002653	2.00	< 0.1326%
22	Level 2	< 0.002653	2.00	< 0.1326%
23	Level 3	< 0.002653	2.00	< 0.1326%
24	Level 3	< 0.002653	2.00	< 0.1326%



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



	Position	Power Density	Limit	% of Limit
25	Level 4	< 0.002653	2.00	< 0.1326%
26	Ground	< 0.002653	2.00	< 0.1326%
27	Level 1	< 0.002653	2.00	< 0.1326%
28	Level 2	< 0.002653	2.00	< 0.1326%
29	Level 3	< 0.002653	2.00	< 0.1326%
30	Level 4	< 0.002653	2.00	< 0.1326%
31	Level 5	< 0.002653	2.00	< 0.1326%
32	Level 1	< 0.002653	2.00	< 0.1326%
33	Ground	< 0.002653	2.00	< 0.1326%
34	Level 1	< 0.002653	2.00	< 0.1326%
35	Level 2	< 0.002653	2.00	< 0.1326%
36	Level 3	< 0.002653	2.00	< 0.1326%
37	Level 4	< 0.002653	2.00	< 0.1326%
38	Level 1	< 0.002653	2.00	< 0.1326%
39	Level 1	< 0.002653	2.00	< 0.1326%
40	Level 1	< 0.002653	2.00	< 0.1326%
41	Level 2	< 0.002653	2.00	< 0.1326%
42	Level 2	< 0.002653	2.00	< 0.1326%
43	Level 2	< 0.002653	2.00	< 0.1326%
44	Level 1	< 0.002653	2.00	< 0.1326%
45	Level 1	< 0.002653	2.00	< 0.1326%
46	Level 2	< 0.002653	2.00	< 0.1326%
47	Level 3	< 0.002653	2.00	< 0.1326%
48	Ground (Outside)	0.003094	2.00	0.1547%
49	Ground	< 0.002653	2.00	< 0.1326%
50	Ground	< 0.002653	2.00	< 0.1326%
51	Level 2	< 0.002653	2.00	< 0.1326%
52	Level 2	< 0.002653	2.00	< 0.1326%
53	Level 3	< 0.002653	2.00	< 0.1326%
54	Ground	< 0.002653	2.00	< 0.1326%
55	Ground	< 0.002653	2.00	< 0.1326%
56	Level 2	< 0.002653	2.00	< 0.1326%
57	Level 1	< 0.002653	2.00	< 0.1326%
58	Ground	< 0.002653	2.00	< 0.1326%
59	Ground	< 0.002653	2.00	< 0.1326%
60	Ground	< 0.002653	2.00	< 0.1326%
61	Ground	< 0.002653	2.00	< 0.1326%
62	Ground	< 0.002653	2.00	< 0.1326%
63	Level 1	< 0.002653	2.00	< 0.1326%
64	Level 1	< 0.002653	2.00	< 0.1326%
65	Level 2	< 0.002653	2.00	< 0.1326%
66	Level 2	< 0.002653	2.00	< 0.1326%
67	Level 3	< 0.002653	2.00	< 0.1326%
68	Level 3	< 0.002653	2.00	< 0.1326%
69	Level 3	< 0.002653	2.00	< 0.1326%
70	Level 3	< 0.002653	2.00	< 0.1326%
71	Level 3	< 0.002653	2.00	< 0.1326%



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)





	Position	Power Density	Limit	% of Limit
72	Level 2	< 0.002653	2.00	< 0.1326%
73	Level 2	< 0.002653	2.00	< 0.1326%
74	Level 1	< 0.002653	2.00	< 0.1326%
75	Level 1	< 0.002653	2.00	< 0.1326%
76	Ground	< 0.002653	2.00	< 0.1326%
77	Ground	< 0.002653	2.00	< 0.1326%
78	Level 1	< 0.002653	2.00	< 0.1326%
79	Level 2	< 0.002653	2.00	< 0.1326%
80	Level 2	< 0.002653	2.00	< 0.1326%
81	Level 2	< 0.002653	2.00	< 0.1326%
82	Level 1	< 0.002653	2.00	< 0.1326%
83	Ground	< 0.002653	2.00	< 0.1326%
84	Ground	< 0.002653	2.00	< 0.1326%
85	Ground	< 0.002653	2.00	< 0.1326%
86	Ground	< 0.002653	2.00	< 0.1326%
87	Ground	< 0.002653	2.00	< 0.1326%
88	Level 2	< 0.002653	2.00	< 0.1326%
89	Ground	< 0.002653	2.00	< 0.1326%
90	Level 2	< 0.002653	2.00	< 0.1326%
91	Level 1	< 0.002653	2.00	< 0.1326%
92	Level 3	< 0.002653	2.00	< 0.1326%
93	Ground	< 0.002653	2.00	< 0.1326%
94	Level 2	< 0.002653	2.00	< 0.1326%
95	Level 1	< 0.002653	2.00	< 0.1326%
96	Level 1	< 0.002653	2.00	< 0.1326%
97	Level 1	< 0.002653	2.00	< 0.1326%
98	Level 2	< 0.002653	2.00	< 0.1326%
99	Level 2	< 0.002653	2.00	< 0.1326%
100	Level 3	< 0.002653	2.00	< 0.1326%
101	Level 3	< 0.002653	2.00	< 0.1326%
102	Level 3	< 0.002653	2.00	< 0.1326%
103	Level 2	< 0.002653	2.00	< 0.1326%
104	Level 2	< 0.002653	2.00	< 0.1326%
105	Level 2	< 0.002653	2.00	< 0.1326%
106	Level 2	< 0.002653	2.00	< 0.1326%
107	Level 3	< 0.002653	2.00	< 0.1326%
108	Level 3 (Walkway C → G)	0.006373	2.00	0.3186%
109	Level 3	< 0.002653	2.00	< 0.1326%
110	Level 3 (Office N3.20)	0.003387	2.00	0.1694%
111	Level 3	< 0.002653	2.00	< 0.1326%
112	Level 3	< 0.002653	2.00	< 0.1326%
113	Level 3 (Office N3.23)	0.003820	2.00	0.1910%
114	Level 2	< 0.002653	2.00	< 0.1326%
115	Level 1	< 0.002653	2.00	< 0.1326%
116	Level 1	< 0.002653	2.00	< 0.1326%
117	Level 1	< 0.002653	2.00	< 0.1326%
118	Ground	< 0.002653	2.00	< 0.1326%



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



	Position	Power Density	Limit	% of Limit
119	Level 1	< 0.002653	2.00	< 0.1326%
120	Level 1	< 0.002653	2.00	< 0.1326%
121	Ground	< 0.002653	2.00	< 0.1326%
122	Level 1	< 0.002653	2.00	< 0.1326%
123	Level 1	< 0.002653	2.00	< 0.1326%
124	Ground	< 0.002653	2.00	< 0.1326%
125	Ground	< 0.002653	2.00	< 0.1326%
126	Ground	< 0.002653	2.00	< 0.1326%
127	Ground	< 0.002653	2.00	< 0.1326%
128	Level 1	< 0.002653	2.00	< 0.1326%
129	Level 1	< 0.002653	2.00	< 0.1326%
130	Ground	< 0.002653	2.00	< 0.1326%
131	Level 2	< 0.002653	2.00	< 0.1326%
132	Level 2	< 0.002653	2.00	< 0.1326%
133	Level 3	< 0.002653	2.00	< 0.1326%
134	Level 3	< 0.002653	2.00	< 0.1326%
135	Level 4	< 0.002653	2.00	< 0.1326%
136	Level 4	< 0.002653	2.00	< 0.1326%
137	Level 5	< 0.002653	2.00	< 0.1326%
138	Level 5	< 0.002653	2.00	< 0.1326%
139	Level 5	< 0.002653	2.00	< 0.1326%
140	Level 6	< 0.002653	2.00	< 0.1326%
141	Level 6	< 0.002653	2.00	< 0.1326%
142	Level 6	< 0.002653	2.00	< 0.1326%
143	Level 7	< 0.002653	2.00	< 0.1326%
144	Level 7	< 0.002653	2.00	< 0.1326%
145	Level 7	< 0.002653	2.00	< 0.1326%
146	Level 8	< 0.002653	2.00	< 0.1326%
147	Level 8	< 0.002653	2.00	< 0.1326%
148	Level 8	< 0.002653	2.00	< 0.1326%
149	Level 1	< 0.002653	2.00	< 0.1326%
150	Level 2	< 0.002653	2.00	< 0.1326%
151	Level 3	< 0.002653	2.00	< 0.1326%
152	Level 3 (Walkway)	0.004483	2.00	0.2241%
153	Level 4	< 0.002653	2.00	< 0.1326%
154	Level 4	< 0.002653	2.00	< 0.1326%
155	Level 4	< 0.002653	2.00	< 0.1326%
156	Level 4	< 0.002653	2.00	< 0.1326%
157	Level 5	< 0.002653	2.00	< 0.1326%
158	Level 5	< 0.002653	2.00	< 0.1326%
159	Level 5	< 0.002653	2.00	< 0.1326%
160	Level 5	< 0.002653	2.00	< 0.1326%
161	Level 6	< 0.002653	2.00	< 0.1326%
162	Level 1	< 0.002653	2.00	< 0.1326%
163	Level 1	< 0.002653	2.00	< 0.1326%
164	Level 2	< 0.002653	2.00	< 0.1326%
165	Level 3	< 0.002653	2.00	< 0.1326%



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



	Position	Power Density	Limit	% of Limit
166	Level 3	< 0.002653	2.00	< 0.1326%
167	Level 3	< 0.002653	2.00	< 0.1326%
168	Level 3	< 0.002653	2.00	< 0.1326%
169	Level 1	< 0.002653	2.00	< 0.1326%
170	Level 1	< 0.002653	2.00	< 0.1326%
171	Level 1	< 0.002653	2.00	< 0.1326%
172	Level 1	< 0.002653	2.00	< 0.1326%
173	Level 1	< 0.002653	2.00	< 0.1326%
174	Level 1	< 0.002653	2.00	< 0.1326%
175	Level 1	< 0.002653	2.00	< 0.1326%
176	Level 1	< 0.002653	2.00	< 0.1326%
177	Level 2	< 0.002653	2.00	< 0.1326%
178	Level 2	< 0.002653	2.00	< 0.1326%
179	Level 2	< 0.002653	2.00	< 0.1326%
180	Level 2	< 0.002653	2.00	< 0.1326%

*Refer to Appendix A for diagram of measurement positions.*

## 8.0 CONCLUSION

Broadband RF EMR Measurements were performed at Deakin University, Burwood campus, located at 221 Burwood Hwy, Burwood, Vic 3125. Measurements were performed outside the buildings and throughout rooms and corridors within the building.

### Broadband RF Field Strengths

All areas surveyed recorded RF exposure levels below limits prescribed by the ARPANSA standard. The highest field strength measured at Deakin University, Burwood campus, located at 221 Burwood Hwy, Burwood, Vic 3125 was 0.3186% of the General Public limit set by ARPANSA RPS3.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd

[www.emctech.com.au](http://www.emctech.com.au)



**Appendix A – Photos of measurement site**



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd  
[www.emctech.com.au](http://www.emctech.com.au)



**Appendix A – Photos of measurement site – Potential RF sources**



## Appendix B – Diagram of measurement positions



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd  
[www.emctech.com.au](http://www.emctech.com.au)





57 Assembly Drive  
Tullamarine VIC 3043  
Phone: 03 9335 3333  
Fax: 03 9338 9260  
www.emctech.com.au

**Figure 1: All Measurement Points**



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd.

www.emctech.com.au

PROJECT No: M060726

DATE: 23-08-2006

DO NOT SCALE

FIGURE 1

LOCATION:  
Deakin University  
Burwood Hwy  
Burwood  
VIC 3125